| | Mor | Mis | | oi Depa ical I1 | | | | | | | | | Rep o | ort | | | | |
|----------------|------------------|---|------------------|--------------------|---------------|------------------------------------|------|-------------------|-------|---------------------------|------|---|---------------------------|--------------|------|---------------------------|---|--|
| FAC | | | | | | | | | EQ ID | | | | | | | | | |
| | Address | | | | | | | City | | | | | | | | | | |
| L | TANK OCATION | Phone | | | | | | Zip | | | | | | | | | | |
| | | Name | | | | | | | | | | | | | | | | |
| TANK OWNER | | | Address | | | | | | | | | | | | | | | |
| | | | City, State, Zip | | | | | | | Phor | ione | | | | | | | |
| TANK | K OPERAT | Phone | | | | | | | | | | | | | | | | |
| | SIR P | Phone | | | | | | | | | | | | | | | | |
| | SIR | Date of SIR Report | | | | | | | | | | | | | | | | |
| | Period C | What is the required number of useable inventory days per tank? | | | | | | | | | | | | | | | | |
| | | | Current Month | | | | | | | Last Month Two Mo Ago | | | | o Mor Ago | nths | | | |
| Tank Number | Tank Contents | 2 44222 | Tank Capacit | <i>y</i> | eak eshold | Minimum Detectable Leak Rate | | ctable Calculated | | Pass/Fail Inconclusive | | | Pass/Fail Inconclusive | | | Pass/Fail Inconclusive | | |
| | | gallons | ٤ | gph | gph | | g | ph | P | F | I | P | F | I | P | F | Ι | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | |
| 1 177 | ık owner is r | . , | <u> </u> | GID. | | | .1 . | .1 60 | th 1 | | 1 6 | | | .1 | | | | |

- 2. Monthly reports must be submitted to federal, state or local agencies upon request.
- 3. If, for any reason, the test is neither "pass" or "fail" the "inconclusive" column must be marked.
- 4. MDEQ must receive verbal notification within 24 hours of receipt of the report for any tank "fail". The SIR report of a failed test must be submitted to MDEQ within 10 days.
- 5. Quantitative and Qualitative SIR Methods:
 - a. A leak threshold, minimum detectable leak rate, and calculated leak rate must be provided for each tank. If not, then the tank failed the SIR test.
 - b. If the calculated leak rate for a tank is greater than or equal to the leak threshold, the tank failed the SIR test. The leak threshold cannot be less than 0.1 gph.
 - c. If the minimum detectable leak rate for a tank is greater than the required performance standard of 0.2 gph and the calculated leak rate is less than the leak threshold, the test is inconclusive for that month.
 - d. A failure, or two consecutive inconclusive results, will require a tank and/or piping integrity test within 15 days from the date of the failure or the date of receipt of the second inconclusive report.

| ť | 5 . | A conclusive | e result of | "pass" | is required | to meet the | e monthly | y leak dete | ection req | uirements. |
|---|------------|--------------|-------------|--------|-------------|-------------|-----------|-------------|------------|------------|
| | | | | | | | | | | |

| o. It conclusive result of pass is i | equired to meet the monthly real detection req | functions: |
|--------------------------------------|--|------------|
| Person conducting evaluation | | |
| Signature | | Date |