BONNER ANALYTICAL TESTING COMPANY

2703 OAK GROVE ROAD, HATTIESBURG, MS 39402 PHONE: (601) 264-2854 FAX: (601) 268-7084



RECEIVED

MAR 2 4 2008

Office of Pollution Control

February 29, 2008

Mr. Tony Russell Office of Pollution Control Mississippi Department of Environmental Quality 101 West Capital Street Jackson, MS 38201 FILECOPY

Re:

Sampling, Analyses, Excavation and Backfilling Work Plan

Gulf Creosote Site, Parcel #5

West Pine Street Hattiesburg, MS

Dear Mr. Russell,

Bonner Analytical Testing Company would like to submit for your review and consideration, the following plan to proceed with sampling of the former Gulf Creosote Site, Parcel #5, located on West Pine Street, to determine if any residual contamination exists.

This plan details the recommended removal, disposal and cleanup of the property in the event any contamination is detected in the analysis of the soil.

Please do not hesitate to call Dr. Bonner or myself if you have any questions.

Respectfully,

Glenn Jones

Cc: Mr. John Fairchild.

WORK PLAN FOR TESTING AND RESTORATION

FOR

Former Gulf States Creosote Site Parcel Number 5 West Pine Street Hattiesburg, Mississippi

Prepared by:

Michael S. Bonner, Ph.D.

Bonner Analytical Testing Company 2703 Oak Grove Road Hattiesburg, MS 39402

February 29, 2008

Table of Contents:

Section	Page
1. Introduction and Work Plan Rationale	1
2. Field Operations	3
3. Schedule	5
4. References	6
List of Figures	
Figure 1- Sight Location	
Figure 2- Site Layout	
Appendix:	
Appendix A- MSDS Creosote	
Appendix B- Analytical report of stump ma around previous contamination	aterial from east side of site on area
Appendix C- Storm Water Pollution Preven	ntion
Appendix D- Site Health and Safety Plan	

1.0 Introduction and Work Plan Rationale

1.1 Objectives/Rationale

- 1.1.1 Objectives
 - 1.1.1.1 Collect core samples from the eastern portion of site.
 - 1.1.1.2 Analyze core samples.
 - 1.1.1.3 Determine necessity and requirements for waste disposal.
 - 1.1.1.4 Complete remediation of property.

1.1.2 Rationale

- 1.1.2.1 Following guidance from the Mississippi Department of Environmental Quality Uncontrolled Sites Branch, the site was grid into five equal sections and three sampling locations were selected on each grid line.
- 1.1.2.2 Once samples are analyzed the site will be delineated horizontally and vertically and disposal needs will be determined.

1.2 Property Background

1.2.1 Property Location and Demographics.

The site is approximately 1.8 acres and is shown in Figure 1 and Figure 2. The site is bound on the north side by West Pine Street, east by Toyota, south by Southern Railroad track, and west by a drainage ditch. The drainage ditch runs southeast to northwest and divides the property roughly into two halves. This document deals with the east half.

1.2.2 Property History

Gulf States Creosote operated a plant in Hattiesburg along West Pine Street from the early 1900's to approximately 1960. In 1962, the site was redeveloped for commercial and light industrial use.

With the finding of the low levels of benzo(a)pyrene, ICON Environmental was contracted to clear the timber, debris and stumps from the site. The tree debris and

shrubs from the entire site were shredded along with the stumps from the western side. The stumps from the eastern side were segregated for shredding. Upon analysis of shredded material no hazardous material, including creosote, were detected.

ICON Environmental then began the process of developing a work plan to test the soil, remove any contamination and finalize remediation of the site. After completion of the needed work for the work plan, ICON Environmental withdrew from the project.

Bonner Analytical Testing Co. (BATCO) has been contracted to complete the work plan for the soil analysis, contamination clean-up and restoration of the site.

1.3 Project History and Detailed Summary of Previous Investigation Activities.

Starting in 1996, Kerr-McGee Chemical (KMC) conducted an investigation of the area. Their findings found low levels of benzo(a)pyrene in soil samples SS-15 (0.033 mg/kg), SS-16 (1.10 mg/kg), and SS-17 (0.93 mg/kg).

1.4 Data Needs and Objectives

- 1.4.1 General Objective: Delineate the extent of contamination in the soil at the site.
- 1.4.2 Specific Objective: Gather sufficient analytical data to develop a three dimensional delineation of creosote constitutes in the soil that exceed the Tier 1 Target Remediation Goals.

1.5 Work Plan Approach

1.5.1 The initial phase of the work plan was developed by ICON Environmental, working through the Uncontrolled Site Branh (USB) of the Mississippi Department of Environmental Quality (MDEQ). This work plan is an extension of previous work, utilizing the same basic strategy while following the Brownfields Work Plan template.

1.5.2 Core samples collected on a systematic grid will be used to delineate the site.

2.0 Field Operations

- 2.1 Soil Delineation
 - 2.1.1 Source Area(s) Characterization
 - 2.1.1.1 As part of a larger investigation, limited surface samples have been previously collected by Kerr-McGee Chemical Co. at the site; however, the extent of the contamination on this parcel is currently not known.
 - 2.1.1.2 The work plan will address the delineation of Parcel Number 5 with respect to creosote contamination.
 - 2.1.2 Extent of Contamination in Soil
 - 2.1.2.1 This Soil Sampling and Analysis Plan (SAP) will utilize the sampling grid previously approved by MDEQ/USB. Six foot core samples will be collected at each sample location. Cores will be divided into three 2-foot sections and transported to Bonner Analytical Testing for analysis.
 - 2.1.2.2 Soil Sampling Objectives
 If contamination is found exceeding the TRG, the horizontal and vertical extent of contamination will be defined utilizing data from soil core analyses. Those areas exceeding the Tier I Remediation Goals (TRG) shall be excavated. Surface clearance samples shall be collected to verify that the remediation efforts were successful. After clearance testing the excavated area will be filled and seeded.
 - 2.1.2.3 Soil Sampling Locations and Frequency
 Waits Engineering Consultants, LLC was
 contracted to grid off the property and to preselect the sampling points. The pre-selected
 points are listed in Figure 2.
 - 2.1.2.4 Soil Sampling Equipment and Procedures Six foot soil cores will be collected using a

mechanical coring device (Geo-probe or equivalent). The cores will be collected in clear "Lexan" coring sleeves. The core sleeves will be split and the soil cores dressed by removing 1/4" of soil from the outer surface. The dressed cores will then be composited into 2-foot sections. The 2-foot cores will be placed in a stainless steel bowl and homogenized. The resulting samples will be placed in pre-cleaned glass wide mouth jars equipped with Teflon lined caps. The jars will be labeled, custody sealed, doubled bagged and stored on ice prior to transport to the laboratory.

Labels and Chain of Custody's will contain the following information as appropriate.

Client Name
Sample location/depth
Date/Time Collected
Analytical Parameter
Preservative
Sample Collector
Sample matrix

All Sampling Equipment shall be decontaminated prior to sampling and then after each six foot core is collected. The DECON procedure will be as follows.

Detergent wash
Tap water rinse
Isopropyl Alcohol Rinse
Deionized water rinse

A minimum of one equipment blank per sampling event, or 20 sample locations, shall be collected. DECON Water will be drummed and tested for the appropriate analytical parameters. Based on test results, the DECON water will either be disposed of as hazardous or non-hazardous waste.

2.1.2.5 Soil Sample Handling and Analysis

Preservation	Type of Container	Shipping	Holding Times	Analytical Method
None	Glass	Ship in Cooler on Ice	Extract/Analyze 14 days /40 days	8310
None	Glass	Ship in Cooler on Ice	Extract/Analyze 14 days /40 days	8270C

2.1.2.6 Special Analysis notes

In accordance with MDEQ-USB guidance all 0-2 ft cores will be analyzed initially. The 2-4ft cores will be analyzed only if 0-2ty cores have detectable concentrations of creosote constituents. Likewise the 4-6ft cores will only be analyzed if the 2-4ft cores have detectable levels of creosote constituents.

2.1.3 Regulatory Involvement Bonner Analytical Testing Co. shall acquire any needed permits from the City of Hattiesburg.

2.2 Site Restoration (Assuming contaminate levels exceed TRG)

2.2.1 Rationale

2.2.1.1 At the digression of the owner and approval by MDEQ-USB the site will be remediated to either meet the "restricted" or "unrestricted" Tier 1 TRG for creosote constituents. If the owner chooses to have the site remediated to the "restricted" TRG, a deed restriction will be attached to the property title. If the owner elects to remediate the site to the "unrestricted" TRG then no deed restriction will be attached to the property title.

2.2.2 Excavation

2.2.2.1 Excavation will be limited to those areas identified in the delineation process as exceeding the TRG (restricted or unrestricted). The excavation will be conducted in a manner such that fugitive dust emissions will be negligible.

- 2.2.2.2 All waste shall be transported in trucks that are covered.
- 2.2.2.3 All activities shall be in accordance with applicable federal, state, and local requirements. All transportation manifests and disposal certificates shall be retained and submitted to BATCO for documentation.
- 2.2.2.4 Prior to backfilling surface clearance samples shall be collected and analyzed.

2.2.3 Backfill

- 2.2.3.1 Once all contaminated soil is removed backfill shall be applied as needed.
- 2.2.3.2 A representative sample of backfill material shall be analyzed by the laboratory to insure that it is non-hazardous
- 2.2.4 Site Stabilization

 For site stabilization and site maintenance refer to Storm

 Water Pollution Prevention in Appendix A.
- 2.2.5 All excavation, refill, and site stabilization activities shall be performed by T.L. Wallace of Columbia, MS under the guidance of Bonner Analytical Testing Co.

3.0 Schedule


Upon completion of this work plan a report will be prepared and submitted to MDEQ. The report will describe all related activities completed during the work. The schedule of activities to be completed under this work plan includes the following:


- 3.1 Utility search to proceed with soil sampling on site
- 3.2 Collect sample cores
- 3.3 Analyze samples
- 3.4 Review results and determine the remainder of the work plan method.
 - 3.4.1 If no contamination is found at the site; a no further action report will be requested from MDEQ.
 - 3.4.2 If contamination is found,
 - 3.4.2.1 Excavate
 - 3.4.2.2 Clearance Testing

- 3.4.2.3 Backfill/re-seed
- 3.4.2.4 Maintenance
- 3.4.2.5 Final Report
- 3.5 With no delays during completion of the fieldwork, the testing and construction phase of work should be completed in approximately 10-19 weeks. With the weekly inspections being completed in approximately 4-12 weeks following restoration.
 - 3.5.1 2 Weeks Utility Search
 - 3.5.2 1 Week Collect core samples
 - 3.5.3 4 Weeks Run analytical test
 - 3.5.4 2 Weeks Review results and work plan determination
 - 3.5.5 1-4 Weeks Excavation
 - 3.5.6 1-4 Weeks Backfill/reseed site
 - 3.5.7 4-12 Weeks Monitor site and drainage.
 - 3.5.8 2 Weeks Final Report

4.0 References

ICON Environmental Solutions, LLC 2003 Work Plan, Former Gulf States Creosote Parcel # 5, Hattiesburg, Mississippi October 15, 2003.





APPENDIX A

MSDS Cresote



Material Safety Data Sheets

产品等有效的 Division of Facilities Services The state of the s

DOD Hazardous Material Information (ANSI Format) For Cornell University Convenience Only

CREOSOTE

Section 9 - Physical & Chemical Properties
Section 10 - Stability & Reactivity D
Section 11 - Toxicological Information
Section 12 - Ecological Information
Section 13 - Disposal Considerations Section 14 - MSDS Transport
<u> muormation</u>
Section 15 - Regulatory Information Section 16 - Other Information

The information in this document is compiled from information maintained by the United States Department of Defense (DOD). Anyone using this information is solely reponsible for the accuracy and applicability of this information to a particular use or situation.

Cornell University does not in any way warrant or imply the applicability, viability or use of this information to any person or for use in any situation.

Section 1 - Product and Company Identification CREOSOTE

Product Identification: CREOSOTE

Date of MSDS: 01/01/1987 Technical Review Date: 10/08/1986 FSC: 6810 NIIN: 00-257-2482

Submitter: GAW Status Code: C MFN: 01

Article: N Kit Part: N

Manufacturer's Information

Manufacturer's Name: KOPPERS CO., INDUSTRIAL PRODUCTS DIV.

Manufacturer's Address2: N/P, NK 00000

Manufacturer's Country: NK General Information Telephone: Emergency Telephone: 412-327-3000 Emergency Telephone: 412-327-3000

MSDS Preparer's Name: N/P

Proprietary: N Reviewed: Y Published: Y CAGE: KO910

Special Project Code: N

Item Description

Item Name: CREOSOTE TECH WOOD

Item Manager: GSA

Specification Number: ASTM D-390

Type/Grade/Class: N/K

Unit of Issue: GL Quantitative Expression: NK

Unit of Issue Quantity: 1 GL CN Type of Container: METAL

Contractor Information

Contractor's Name: KOPPERS CO INC

Contractor's Address1: 3000 KOPPERS BLDG

Contractor's Address2: PITTSBURGH, PA 15219-1818

Contractor's Telephone: UNKNOWN

Contractor's CAGE: 80592

Contractor Information

Contractor's Name: KOPPERS CO., INDUSTRIAL PRODUCTS DIV.

Contractor's Address1: UNKNOWN

Contractor's Address2: UNKNOWN, NK 00000

Contractor's Telephone: UNKNOWN

Contractor's CAGE: KO910

Section 2 - Compositon/Information on Ingredients CREOSOTE

Ingredient Name: CREOSOTE (SARA III)

Ingredient CAS Number: 8001-58-9 Ingredient CAS Code: M

RTECS Number: GF8615000 RTECS Code: M

=WT: =WT Code:

=Volume: =Volume Code:

>WT: >WT Code:

http://msds.ehs.comell.edu/msds/msdsdod/a31/m15390.htm

>Volume: >Volume Code:

<WT: <WT Code:

<Volume: <Volume Code:

% Low WT: % Low WT Code: % High WT: % High WT Code:

% Low Volume: % Low Volume Code:

% High Volume: % High Volume Code:

% Text: N/P

% Environmental Weight: Other REC Limits: N/P

OSHA PEL: NOT ESTABLISHED OSHA PEL Code: M

OSHA STEL: OSHA STEL Code:

ACGIH TLV: NOT ESTABLISHED ACGIH TLV Code; M

ACGIH STEL: N/P ACGIH STEL Code:

EPA Reporting Quantity: 1 LB DOT Reporting Quantity: 1 LB Ozone Depleting Chemical: N

Section 3 - Hazards Identification, Including Emergency Overview CREOSOTE

Health Hazards Acute & Chronic: N/P

Signs & Symptoms of Overexposure:

IRRIT TO SKIN & EYES. VAPOR & FUMES EVOLVED ON HEATING IRRIT TO EYES &

Medical Conditions Aggravated by Exposure: N/P

LD50 LC50 Mixture: N/P

Route of Entry Indicators:

Inhalation: N/P Skin: N/P Ingestion: N/P

Carcenogenicity Indicators

NTP: NT IARC: N/P OSHA: N/P

Carcinogenicity Explanation: N/P

Section 4 - First Aid Measures **CREOSOTE**

First Aid:

359595555555

REMOVE TO FRESH AIR.IF NOT BREATHING.GIVE ARTIFICIAL RESPIRATION, PREF MOUTH TO MOUTH.IF BREATHING IS DIFFICULT, GIVE OXYG.CALL A PHYS.INCASE OF

http://msds.ehs.comell.edu/msds/msdsdod/a31/m15390.htm

3/24/2003

SKIN OR EYE CONTACT, REMOV FR SKIN W/WATERLESS HAND CLEAN ER; FLUSH EYES IMMED W/PLENTY OF WATER F/AT LEAST

CREOSOTE

Section 5 - Fire Fighting Measures

Fire Fighting Procedures:

FULL PROTECTIVE EQUIPMENT INCL SELF-CONTAINED BREATH APPARAT Unusual Fire or Explosion Hazard:

IN CLOSED CONTAINERS CONTAINING LIQUID, PRESSURE BUILD-UP DUE TO HEAT EXPOSURE.WATER MAY BE US

Extinguishing Media:

CARBON DIOXIDE, WATERFOG, FOAM, DRY CHEMICAL

Flash Point: Flash Point Text: >200F TCC >93C

Autoignition Temperature:

Autoignition Temperature Text: N/A

Lower Limit(s): Upper Limit(s):

Section 6 - Accidental Release Measures CREOSOTE

Spill Release Procedures:

CLEAN UP & PUT BACK IN CONTAINER OR WASTE RECEPTABLE.COVER W/LAYER OF SAND & SCRAPEUP.USE PROTECTIVE MEASURES OUTLINED IN SECTION VIII.DO NOT ALLOW TO GET INTO STREAM.

Section 7 - Handling and Storage CREOSOTE

Handling and Storage Precautions:

Other Precautions:

Section 8 - Exposure Controls & Personal Protection CREOSOTE

Repiratory Protection:

WHEN EXPOS ARE ABOVE TLV/SEC.II & V) & VENTIL IS INADEQUATE,USE APPR Ventilation:

LOC EXHAUST-USE ADEQ VENTIL IN VOLUME & PATTERN TO KEEP WORK

RUBBER(NEOPRENE

Eye Protection: CHEM SAFETY GOGG AND/OR F

Other Protective Equipment: OVERALLS OR A NEOPRENE APRON TO PROTECT AGAINST

Work Hygenic Practices: N/P

Supplemental Health & Safety Information: N/P

Section 9 - Physical & Chemical Properties CREOSOTE

HCC: N1

NRC/State License Number:

Net Property Weight for Ammo:

Boiling Point: Boiling Point Text: 7356F 180

Melting/Freezing Point: Melting/Freezing Text: N/A Decomposition Point: Decomposition Text: N/A

Vapor Pressure: 1 Vapor Density: >1 Percent Volatile Organic Content:

Specific Gravity: 1.050

Volatile Organic Content Pounds per Gallon: nH: N/P

Volatile Organic Content Grams per Liter:

Viscosity: N/P

Evaporation Weight and Reference: SLOW

Solubility in Water: SLIGHT

Appearance and Odor: BROWN TO BLACK LIQUID W/CREOSOTE OR TARRY ODOR Percent Volatiles by Volume: N/P

Corrosion Rate: N/P

Section 10 - Stability & Reactivity Data **CREOSOTE**

Stability Indicator: YES Materials to Avoid:

N/P

Stability Condition to Avoid:

OVERHEATING

Hazardous Decomposition Products:

Hazardous Polymerization Indicator: NO

Conditions to Avoid Polymerization:

Section 11 - Toxicological Information CREOSOTE

Toxicological Information: N/P

Section 12 - Ecological Information CREOSOTE

Ecological Information:

N/P

999999

Section 13 - Disposal Considerations CREOSOTE

Waste Disposal Methods:

http://msds.ehs.comell.edu/msds/msdsdod/a31/m15390.htm

3/24/2003

BURN IN APPRVD INCINERATOR OR USE APPRVD CHEMICALLY DISPOSAL FACILITY.DO NOT INCINERATE CLOSED CONTAINER DISPOSAL MUST BE CARRIED OUT IN ACCORDANCE W/LOC, STATE & FEDERAL REGULATIONS.

Section 14 - MSDS Transport Information CREOSOTE

Transport Information:

N/P

Section 15 - Regulatory Information CREOSOTE

SARA Title III Information:

Federal Regulatory Information:

N/P

State Regulatory Information:

N/P

Section 16 - Other Information CREOSOTE

Other Information:

N/P

HMIS Transportation Information

Product Identification: CREOSOTE Transporation ID Number: 62009 Responsible Party CAGE: KO910 Date MSDS Prepared: 01/01/1987 Date MSDS Reviewed: 01/22/1983

MFN: 01/22/1983 Submitter: GAW Status Code: C

Container Information

Unit of Issue: GL

Container Quantity: 1 GL CN Type of Container: METAL

Net Unit Weight:

Article without MSDS: N

Technical Entry NOS Shipping Number:

Radioactivity:

Form:

Net Explosive Weight:

Coast Guard Ammunition Code:

Magnetism: N/P

AF MMAC Code:

DOD Exemption Number:

Limited Quantity Indicator:

http://msds.ehs.cornell.edu/msds/msdsdod/a31/m15390.htm

3/24/2003

Multiple Kit Number: 0

Kit Indicator: N Kit Part Indicator: N Review Indicator: Y Additional Data:

Department of Transportation Information

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION DOT PSN Code: ZZZ

Symbols: N/R

DOT PSN Modifier: Hazard Class: N/R UN ID Number: N/R

DOT Packaging Group: N/R

Label: N/R

Special Provision(s): N/R Packaging Exception: N/R Non Bulk Packaging; N/R Bulk Packaging: N/R

Maximimum Quanity in Passenger Area: N/R Maximimum Quanity in Cargo Area: N/R

Stow in Vessel Requirements: N/R Requirements Water/Sp/Other: N/R

IMO Detail Information

IMO Proper Shipping Name: SEE ADDITIONAL DATA FIELD IN HMIS FOR FURTHER

IMO PSN Code: XXX IMO PSN Modifier:

IMDG Page Number: N/A

UN Number:

UN Hazard Class: N/A IMO Packaging Group: Subsidiary Risk Label: EMS Number: N/A

Medical First Aid Guide Number: N/A

IATA Detail Information

IATA Proper Shipping Name: SEE ADDITIONAL DATA FIELD IN HMIS FOR FURTHER **INFORMATION**

IATA PSN Code: XXX IATA PSN Modifier: IATA UN Id Number: IATA UN Class:

Subsidiary Risk Class: **UN Packaging Group:**

IATA Label:

Packaging Note for Passengers:

Maximum Quantity for Passengers:

Packaging Note for Cargo:

Maximum Quantity for Cargo:

Exceptions:

http://msds.ehs.cornell.edu/msds/msdsdod/a31/m15390.htm

AFI Detail Information

AFI Proper Shipping Name: SEE ADDITIONAL DATA FIELD IN HMIS FOR FURTHER

AFI Symbols:

AFI PSN Code: XXX AFI PSN Modifier:

AFI UN Id Number: N/A AFI Hazard Class: N/A AFI Packing Group: N/A

AFI Label:

Special Provisions: N/A Back Pack Reference: N/A

HAZCOM Label Information

Product Identification: CREOSOTE

CAGE: KO910

Assigned Individual: Y

Company Name: KOPPERS CO., INDUSTRIAL PRODUCTS DIV.

Company PO Box:

Company Street Address1: UNKNOWN

Company Street Address2: UNKNOWN, NK 00000 NK

Health Emergency Telephone: 412-327-3000

Label Required Indicator: Y Date Label Reviewed: 12/16/1998

Status Code: C

Manufacturer's Label Number:

Date of Label: 12/16/1998 Year Procured: N/K Organization Code: G

Chronic Hazard Indicator: N/P Eye Protection Indicator: N/P Skin Protection Indicator: N/P

Respiratory Protection Indicator: N/P

Signal Word: N/P Health Hazard: Contact Hazard: Fire Hazard:

Reactivity Hazard:

8/7/2002 9:42:54 PM

APPENDIX B

Analytical report on contaminated Stump material from east portion of site

CULPEPPER TESTING LABORATORIES

301 HARDY STREET SUITE D HATTIESBURG, MS 39401 (601) 583-0411 FAX: (601) 582-8163 E-mail: culpe@aol.com

CLIENT: ICON ENVIRONMENTAL SOLUTIONS

REPORT DATE:

09-17-03

COLLECTED BY:

JOE FORD

SAMPLE DATE:

08-27-03

COMMENTS: SHREDDED TREE STUMPS

DATE ANALYZED:

08-28-03

CTI SAMPLE ID

*****	ŞEI	AI-AÖİ	ATILE	CTL JOB N		20030429
ANALYTE	RESU	LT	UNITS	REPORT	,	EPA
ACENAPHTHEM	ND		mg/kg	5.98	FACTOR	METHO
VOENYDITHALENE	MD		rigilig		5	8270C
ANTHRACENE	ND			5.98	5	82706
BENZO(a)ANTHRACENE	ND		ng/kg	5.98	5	8270C
BENZO(a)PYRENE			ng/kg	5.98	5	8270C
BENZO(b)FLUORANTHENE	ND	1	ig/kg	5.98	5	8270C
BENZO(g,h,i)PERYLENE	ND ND	_ m	g/kg	5.98	5	8270C
BENZO(K)FLUORANTIJENE	ND	m	gilig	5.98	5	8270C
	ND	in	ÿ/kg	5,98	3	8270C
4-BROMOPHENYLPHENYLETHER	ND	55%	ykg	5.98	5	
BUTYLBENZYLPHTHALATE	. ND	mg	/kg	5.98	5	8270C
ARBAZOLE	ND	mg	/ka	5.98		8270C
-CHLORO-3-MEHTYLPHENOL	ND	mg/		5.98	5	8270C .
-CHLOROANILINE	ND	 	- -		5	8270C
15(2-CHLONGEITHOAT JUNE ITHING	שֿוּא	mg/	- -	5.98	5	8270C
SO CHI OBOETHYI JETHER		uigr		0.50	5	OZIVU
S(2-CHLOROISOPROPYL)ETHER	ND	mgA	9	5.98	5	8279C
TOTAL STATE IN THE STATE OF THE	ЙD	mg/k	g (5.98	5	8270C

CULPEPPER TESTING LABORATORIES

301 HARDY STREET SUITE D HATTIESBURG, MS 39401 (601) 583-0411 FAX: (601) 582-8163 E-mail: culpe@aol.com

CLIENT: ICON ENVIRONMENTAL SOLUTIONS

REPORT DATE:

09-17-03

COLLECTED BY:

JUE FORD

SAMPLE DATE:

08-27-03

COMMENTS: SHREDDED TREE STUMPS

DATE ANALYZED:

08-28-03

CTL SAMPLE ID:

	SEM	FAOFT	E	NUMBER:	20030429
ANALYTE	RESUL	TUNIT	and the second		EPA
2-CHLORONATHTHALENE	ND		LIMITS	17.0101	METHOL
3.CHLOBODHENCH	MD	กาศูกิสุ		5	02/00
4-CHLOROPHENYLPHENYLETHER		mg//s	5,98	5	3278C
CHRYSENE	NO	malka	5.98	5	8270C
DIBENZOFURAN	ND	mg/kg	5.98	5	8270C
	ND	mg/kg	5.98	5	8270C
DIBENZ(a,h)ANTHRACENE	ND	mg/kg	5.98	5	1
1,2-DICHLOROBENZENE	ND	mg/kg	5.98	5	8270C
1,3-DICHLOROBENZENE	ND	unging	5.56		8270C
1 4 DICHLOROBENZENE	ND		f	5"	ÖZTÜL
3.3'-DICHLOROBENZIDINE	ND	mg/kg	5.98	5	8270C
,4-DICHLOROPHENOL		mg/kg	5.98	5	8270C
HETHYLPHTHALATE	ND	mg/kg	5.98	5	8270C
4-DIMETHYLPHENOL	ND	mg/kg	5.98	5	8270C
METHYLPHINALATE	ND	rng/kg	5.98	5	8270C
	ND	підіку	5.96	ō	
M.BIITYI PHTHALATE	ND	mg/kg	5.98	5	8270C 8270C

CULPEPPER TESTING LABORATORIES

301 HARDY STREET SUITE D HATTIESBURG, MS 39401 (601) 583-0411 FAX: (601) 582-8163

E-mail: cuipe@aol.com

CLIENT: ICON ENVIRONMENTAL SOLUTIONS

REPORT DATE:

09-17-03

COLLECTED BY:

JOE FORD

SAMPLE DATE:

08-27-03

COMMENTS: SHREDDED TREE STUMPS

DATE ANALYZED:

08-28-03

	SEN	L-VOLATILE	CTL JOB NU		0030429
ANALYTE	RESU	LT UNITS	REPORT	DIL. FACTOR	EPA METHOD
1,6 DINITIO 2 METHYLYNENOL	ND	mg/kg	5.98	5	
2.4-C:NITROPHENOL	ND	mg/kg	5.98	5	8270C
2,4-DINTROTOLUENE	ND	mg/kg	5.98		8270C
2,6-DINTROTOLUENE	ND	mg/kg	5.98	5 -	8270C
DI-N-OCTYLPHTHALATE	ND	mg/kg		5	8270C
FLUORANTHENE	ND	· ·	5.98	5	8270C
TLUCRENE	ND	mg/kg	5.98	5	8270C
HEXACHLORGRENZENF	 	mg/kg	5.98	5	8270C
HEXACHLOROBUTADIENE	ND	mg/kg	5.08	<u>5</u> .	8270C
HEXACHLOROCYCLOPENTADIENE	ND	mg/kg	5.98	-5	8270C
HEXACHLOROETHANE	ND	mg/kg	5.98	5	8270C
	ND	mg/kg	5.98	5	8270C
INCEMO(1,2,3-CD)PYRENE	ND	mg/kg	5.98	5	8270C
SUPHURONE	ND	mg/kg	5.98	5	8270C
METHYLNAPHTHALENE	MD	mg/kg	5.98	5	8270C
METHYLPHENOL	ND	mg/kg	5.98	5	8270C
LP-METHYLPHENOL	ND	mg/kg	5.98	5	
APHTHALENE	ND	mg/kg	5.98	5	8270C 8270C

6015828163

CULPEPPER TESTING LABORATORIES

301 HARDY STREET SUITE D HATTIESBURG, MS 39401 (601) 583-0411 FAX: (601) 582-8163 E-mail: cuipe@aol.com

CLIENT: ICON ENVIRONMENTAL SOLUTIONS

REPORT DATE:

09-17-03

COLLECTED BY:

JOE FORD

SAMPLE DATE:

08-27-03

COMMENTS: SHREDDED TREE STUMPS

DATE ANALYZED:

08-28-03

ANALYTE			ATE			20030429
	RESU	LT	UNITS	REPORT	DIL. FACTOR	EPA METHOL
2-NITROLINE	DN		mg/kg	5.98	5	
3-NITROANILINE	ND	1	mg/kg	5.98	5	82700
4-NITROANILINE	NO		mg/kg	5.98	5	8270C
NITROBENZENE	ND		ng/kg	5.98	5	8270C
2-NITROPHENOL	ND		ng/kg	5.98		8270C
4-NITROPHENOL	ND	-	ng/kg	5.98	5	8270C
N-NITROSODI-N-PROPYLAMINE	ND"	1	g/kg	5.98	5	8270C
N-HITROSODIPHENLAMINE	ND	1	ging		5	8270C
PENTACHLOROPHENOL	ND	+-	gray g/kg	5.98	5	8270C
PHENANTHRENE	ND	 		5.98	5 /	9270C
HENOL	MD	 	J/kg	5.98	5	8270C
YRENE		 	/kg	5.98	5	8270C
IS(2-ETHYLHEXYL)PHTHALATE	ND	-	/kg	5.98	5	8270C
2,4-TRICHLOROBERLENE	ND	mg	/kg	5.98	5	8270C
4,5-TRICHLOROPHENOL	ND	mg.	kg	5.98	5	8270C
.6-TRICHLOROPHENOL	MD	mgi	kg	5.98	5	8270C
ND = NON DETECT	ND	mg/	kg	5.98	5	8276C

APPENDIX C

Storm Water Pollution Prevention

Storm Water Pollution Prevention

1. Site Identification

The site is presently clear of timber and west side of the property has been reseeded with permanent grass for ground cover. The sampling of the soil will not disturb the area of the drainage ditch, or it's immediate surroundings. Three-fourths of the site has low erosion hazard. The remainder of the site has low to medium erosion hazard. On the south end o the property an earthen ditch is positioned east to west that flows into an earthen ditch positioned southeast to northwest. The ditches have intermittent flow with the direction of flow being from southeast to northwest, draining into Gordon's Creek, which is not on the 303(d) list for siltation, turbidity, or habitat alterations. Therefore, additional controls that are warranted for a site discharging to listed receiving streams are not required.

2. Controls

Vegetative Controls: After completion of the sampling and finalizing the remediation of the property, the eastern portion will be seeded (permanent seeding) within seven calendar days.

Structural Controls: A construction entrance will be built and accumulation of mud on vehicle tires will be washed, if needed, during muddy conditions.

Housekeeping Practices: All Equipment maintenance and repair will be done offsite. Trashcans will be placed onsite as needed. Paints, solvents, fertilizers, or any other potentially toxic materials will not be stored on site.

Post construction/Storm Water Management Measures: Additional vegetative and structural controls will be placed onsite as needed.

3. Implementation Sequence

1/ Pull Soil samples

2/Perform analytical tests.

3/ Identify any contamination

4/ Excavate contamination

5/ Remove and dispose cont. 6/ Backfill, if needed

7/ Reseed eastern portion

8/ Maintenance plan

4. Maintenance Plan

Check all disturbed areas, erosion and sediment controls after each significant rainfall but not less than once per week. Make needed repairs within 24 hours. Replace non-functional silt fence. Maintain all vegetated areas to provide proper ground cover- reseed and fertilize as needed.

APPENDIX D

SITE HEALTH AND SAFETY PLAN

HEALTH AND SAFETY PLAN (HASP)

1. Plan Overview

The project activities consist of pulling core samples to a minimum depth of 6 feet. Collecting a sample from each two-foot section of the core, and performing analytical test of sample material to determine if contamination is present. If any contamination is found the landowner(s) will decide whether to cease all work and leave the property as the designated plan in Phase I work plan, or continue work to excavate contamination, remove and dispose of contaminated material in the proper landfill and backfill if needed. Clean backfill will be transported from an off-site location and placed as needed on-site. All transportation and removal of contaminated material shall be managed I accordance with all applicable Federal, State, and local requirement. All transportation manifests and disposal certificates shall be retained and submitted to ICON for documentation. The site is bound to the west by the drainage ditch, to the south by Southern Railroad track, to the east by Strahan Auto Sales, and to the north by West Pine Street. A site location map is provided as Figure 1 and Figure 2.

Glenn Jones, Bonner Analytical Testing Co. Health and Safety Officer	Date
Dr. Michael S. Bonner, CEO Bonner Analytical Testing Co.	Date

2. Staff Organization

Project Manager Dr. Michael S. Bonner- As Project Manager on this site, Dr. Bonner will assume responsibility for the overall co-ordination of on-site and off-site activities.

Site Safety Officer Glenn Jones-As Site Safety Officer ((O, Mr. Jones will be responsible for collecting and maintaining documentation of each worker, conducting and documentation of daily tool box safety meeting, and maintenance of current emergency response and medical assistance phone numbers throughout the project.

Alternate Site Safety Officer(s)	Dr. Michael S. Bonner Chris Bonner Eric Sanford	(BATCO) (BATCO) (BATCO)
	David Kanoly	(BATCO)

- Will assume the duties of the SSO when the SSO is not on the project site.

<u>Technicians / Operators</u> Will be responsible for heavy equipment operation and general labor on the site. They will report directly to the Project Manager or SSO.

3 Work Activities

<u>Pre-construction site reconnaissance</u>

This activity will consist of a general recognizance of the site to include locating underground and aboveground utilities and structures that may be present onsite that could be affected by site activities.

Setting preliminary grid to identify core locations This activity consists of the orientation of five core locations on the eastern portion of the site.

Pulling Core Samples
Pull five (5) core samples down to a depth of ten (10) feet and then use a PID (Photo Ionization Device) to identify the strongest contamination point of each of the five samples. The section of the highest reading will be analyzed for contamination. If no contamination purposes.

Run Analytical Test & Review Results

This activity will determine if any contamination is evident in the soil on the eastern portion of the site. (1) If none is found, no other work will be done other than reseed the eastern portion and complete the maintenance profile. (2) If contamination is found, the decision will be made by the landowners on whether to cease work and leave the property "capped" as it is. Or (3) excavate the contaminated soil, remove and dispose of in the proper landfill, and backfill the property as needed and perform maintenance.

Backfilling This activity consists of backfilling the site as needed with clean soil from offsite. The backfill shall be free from roots, trash, debris, frozen material, and stones larger than 3

Storm water Pollution Prevention This activity may consist of one or all of the following: Vegetative controls, structural controls, housekeeping practices, post construction/storm water management measures, implementation, and maintenance.

4 Hazard Assessment

Previous environmental assessments indicate that chemical hazards are not present on this site. However, all precautions will be taken to ensure that no site worker comes in contact with any suspicious looking materials (soils, liquids). In the event suspicious materials are encountered, site workers will cease in that area and all appropriate notifications will be made. All site workers will be briefed on the site's previous creosoting activities and the hazards associated with exposure to creosote. An MSDS for Creosote is included as Appendix A in this document and will be reviewed with all site workers.

5 General Health and Safety Requirements

In the event an ICON Environmental employee or subcontractor is exposed to a known on-site chemical hazard, that person will then be examined by a qualified medical doctor.

All accidents will be immediately reported to the SSO who will report them immediately to the project manager. The project manager will make the necessary notifications as appropriate. Local emergency services may be called to the site by dialing 911.

If an off-site chemical hazard is identified the subject area will be deemed an exclusion zone. Access to the exclusion zone will be limited to persons in compliance with 29 CFR 1910.120 (HAZWOPER).

No work will be performed during periods of lightning, or other severe weather conditions. No work will be performed in any exclusion zones, or in excavations, which are not in compliance with OSHA regulations related to trenches.

Appropriate PPE and work area visual observations will be conducted as determined by SSO.

6 Site Specific Health and Safety Requirements

It is expected that work on this site will be conducted in Level D, generally consisting of hardhat, steel toed boots/shoes, gloves, safety glasses, and hearing protection (as needed). Decontamination at this level will consist of washing shoes/boots upon leaving site and a recommendation to immediately change, or wash daily work clothes upon returning to home/hotel.

Heavy Equipment that is used on-site which comes in contact with contaminated soil will be washed either with potable water and detergent, or with potable water via a pressure washer. The rinsate will either be collected and disposed of off-site or sent to the local POTW, or storm sewer. Disposal to the POTW or storm sewer will be pursued first and ICON Environmental will obtain any necessary permits.

7 Emergency Response Procedures

The nearest medical facility is Forrest General Hospital and may be contacted directly by dialing 288-2100. Emergency medical services may be called to the site by dialing 911. The site has no land based telephone service, cell phones will be maintained on-site at all times in case of emergency.

A map showing the route to and from the site to Forrest General Hospital is included as Figure 1.

8 Logs, Reports, and Record Keeping of Health and Safety Documents

Daily tool box safety meetings will be held and documented on the Daily Tool Box Safety Meeting form. This documentation will be maintained by ICON Environmental. The daily tool box safety meeting form is presented below.

Documentation to establish compliance with 29 CFR 1910.120 for each employee will be maintained on-site by the SSO.

The undersigned have read and understand the site safety plan and agree to comply with all requirement listed.

Name (printed)	Name (signed)	Date
-		
,		

Daily Tool Box Safety Meeting Form ICON Environmental Solutions, LLC

Location	per / Name:			Date:
		N	Aeeting conduct	ed by:
Time started:		Time end	led [.]	Total minutes:
Project Manag	er:	Q:	ita Safat am	Total minutes:
Alternate Site S	Safety Officer:	Si	ne salety Office	PT:
1) Daily so	cope of work topics			_
A)	ope of work topics			
B)				
2) Daily Ch	nemical / Physical H	azarde		
α_j	<i>y</i>			
B)				
Chemical	Exposure Limit	Exposure Route	Symptom	Physical
				Hazards
_			<u>-</u>	
•				
•				
Accidents	Reviewed:		_	
) Storm Wate	er Controls Necessa	tv? Voc./	* X T	
		·): 168/	INO	List Control Measures
Comments	/ Suggestions			•
	/ Suggestions:			
Personal Pro	otective Levels / Ta	ska:		
evel	PPE Description	Į.	Work Task	Type Cartridge
				
		~		
		7		

7) Signed by Those in Attendance:

Name (printed)

Name (signature)

Company